

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 61-292571

(43)Date of publication of application : 23.12.1986

(51)Int.Cl.

G01R 13/32

(21)Application number : 60-134092

(71)Applicant : HITACHI LTD

(22)Date of filing : 21.06.1985


(72)Inventor : IKEUCHI FUMIO
INOUE FUMIHITO

(54) TRIGGER SIGNAL GENERATION CIRCUIT

(57)Abstract:

PURPOSE: To enable the generation of a trigger signal both as such to be created sequentially and as unable to be determined primarily, by having the results of comparison of a first comparator circuit ANDed with the results of comparison of a second comparator circuit by an AND circuit once delayed by a fixed time to obtain a trigger signal.

CONSTITUTION: An input signal DATAIN is inputted into comparator circuits 5 and 6 as maskable in LSB side bits with AND gate groups 3 and 4 on the basis of data from a mask register 10 while trigger conditions are inputted into the circuits 5 and 6 from registers 1 and 2 and the comparator circuits 5 and 6 compare the signal DATAIN with the trigger condition. After being set on a D type FF7 in which a clock signal CLK synchronous to the signal DATAIN is already inputted as a setting signal, the results of comparison from the circuit 5 are ANDed with the results of comparison from the circuit 6 by an AND gate 8. Thus, a D type FF9 is allowed to be set only when the AND output of '1' is obtained from the AND gate 8 and the set output given at this time is obtained as a trigger signal.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office